METHVEN

DESIGNED NEW ZEALAND & ENGINEERED

WALL MOUNTED SWIVEL 197MM SPOUT - CHROME



CONSTRUCTION: Brass
CARTRIDGE/VALVE TYPE: N/A
SUPPLY: Suitable For Low Pressure Systems
INLET CONNECTIONS: ½” BSP
WORKING PRESSURES: 0.1 - 5.0 BAR
OPERATION: N/A

- Durable Brass Body Construction
- Swivel Outlet
- Slim Stream Aerator With Directional Swivel

WSP03CP | **Chrome**

Open Outlet Flow (Bar - l/min)

BAR	0.1	0.3	0.5	1.0	2.0	3.0	4.0	5.0
SPOUT FLOW	4.2	6.4	8.2	11.3	16	21.5	24.4	25.2

kiwa approved KUKreg4 ATS 3
2110702

WRAS APPROVED PRODUCT
2110318

20 YEAR WARRANTY* TERMS & CONDITIONS APPLY

Please Note: Flow rate will be dictated by installation configurations.
Please ensure to check the appropriate flow restrictor information if applicable.
***Please refer to website for full warranty details.**

FREEPHONE: 0800 195 1602 | FAX ORDERS: 08444 068 690 | EMAIL: SALES@UK.METHVEN.COM methven.com

THE INFORMATION ON THIS SPECIFICATION DOCUMENT WAS CORRECT AT THE DATE OF ISSUE. SOME VARIATION MAY OCCUR DUE TO THE MANUFACTURING TOLERENCES AND SITE SPECIFIC CONDTIONS.